



### Technical Data

|                  |               |
|------------------|---------------|
| Gross capacity   | 56 L          |
| Net capacity     | 50 L          |
| Height           | 1,450 mm      |
| Outside diameter | 600 mm        |
| Empty weight     | ± 156 kg      |
| Boil-off rate    | 2.0 L/day     |
| Storage Pressure | 0 - 12 bar g. |
| MAWP             | 12 bar g.     |

### Features

- Stainless steel welded construction
- Vapor cooled shield technology
- Easily removable filling line
- Vacuum insulated bayonet connection
- Mobile build
- Two (2) relief valves
- Vacuum and multi-layer insulation
- Two-year vacuum warranty

### Options

- Pressure build unit (custom)
- ASME, KGS certification
- Accessories: Vacuum Jacketed transfer line

### Vacuum Jacketed Transfer Line


#### Connection (inlet-outlet)

- Bayonet female - bayonet female
- Bayonet female - bayonet male
- Bayonet female - 1/4" dual ferrule tube

#### Length

- 2 meter
- 5 meter
- Other (custom)

### Schematic



|      |                            |
|------|----------------------------|
| V-1  | Liquid in/out valve        |
| V-2  | Gas vent valve             |
| V-3  | Pressurizing valve         |
| RV-1 | Relief valve 1 (11.4 barg) |
| RV-2 | Relief valve 2 (12.0 barg) |
| PG   | Pressure gauge             |

\*Available in two models:  
HYST - 50  
HYST - 250